

Information

OpenStage HFA/SIP

The Open Unified Communications telephones.

OpenStage is a new generation of phones which sets the benchmark for open and unified communications.

These stylish devices provide an intuitive and engaging communication experience, incorporating innovative features.

OpenStage is the prelude to a new era of high quality and user-oriented communications solutions that, through their design concept, sustainably protect the environment and are distinguished by high energy efficiency.

Communication for the open minded

Siemens Enterprise Communications
www.siemens-enterprise.com

SIEMENS

Overview of OpenStage

The OpenStage family is intuitive in functionality and interface, integrated through interoperability with other devices, and multimodal to allow access to various services and applications.

The OpenStage family is designed to be extremely user friendly and simplify feature implementation. Sensorial interfaces based on advanced technology solutions (touch keys, embedded color LEDs, TouchSlider for volume control and TouchGuide navigator) as well as large, tiltable, backlit color graphical displays in TFT technology facilitate user interaction.

Soft-labeled (paperless phone) touch sensor keys can be easily programmed for specific phone functions, line/feature access or speed dial by name. An ideal solution for office applications where mobility and flexibility are important factors.

Fixed feature/function keys enable easy access to frequently used phone functions such as Drop/Release, Call Forwarding, Speaker and dedicated applications such as Phonebook, Call Log/History, Answering Machine.

OpenStage incorporates the latest developments in leading edge acoustics to ensure delivery of the very best voice quality on the handset and speakerphone (thanks to the handset design, speaker model, housing dimensions and G.722 wideband codec). A high quality speakerphone is built in as standard in all models (exception OpenStage 20 E).

OpenStage design highlights include variation of materials and colors (from molded plastic in ice blue or lava to high-end silver blue metallic lacquering and brushed aluminum).

The OpenStage IP phone family comprises the following models:

- OpenStage 15 (ice blue or lava)
- OpenStage 20 E (ice blue or lava)
- OpenStage 20 (ice blue or lava)
- OpenStage 40 (ice blue or lava)
- OpenStage 60 (ice blue or lava)
- OpenStage 80 (silver-blue metallic)

Each model is available as a phone variant with the open standards for SIP voice communication or with the proprietary protocol of Siemens Enterprise Communications (CorNet-IP, also known as HFA = HiPath Feature Access).

In addition to the standard-based SIP (RFC 3261) VoIP protocol, OpenStage SIP phones support even more features such as consultation, local 3-way conference, multilines and team features that allow a high degree of flexibility in your IT strategy.

The OpenStage CorNet-IP variants provide a favorable access to the wide range of features of the HiPath platforms 3000/5000 and 4000 as well as the OpenScape Office LX/MX together with an innovative user interface.

Each OpenStage IP phone provides an integrated Ethernet switch. The network is accessed by 10/100 Base-T or as a variant via Gigabit Ethernet (exceptions: OpenStage 15 and OpenStage 20 E).

All phones support 802.3af Power over LAN.

OpenStage telephones are easy to deploy and ongoing administration is simple.

The telephones can be centrally managed as part of an IT environment.

OpenStage 15 is a universal solution for efficient and professional telephony. Each succeeding model has increased feature capabilities and perceived value culminating in the high-end OpenStage 80 model targeted at top level managers and executives.

Product family

OpenStage 15

OpenStage 15 is a full-featured speakerphone with display and eight function keys with LEDs that could be used for line keys when operated as a multi-line telephone, for example.

Display

- Graphical display, 2 lines monochrome (not tiltable)

Keys

- Keypad
- 3 fixed function keys with red LEDs
- 8 freely programmable keys with red LEDs (upgradeable with Key Module)
- Paper labels
- Control keys +/-
- 3 navigation keys

Acoustics

- Hands free talking (full duplex)

Wall-mountable



The telephones **OpenStage 15 SIP**, **OpenStage 20 SIP** and **OpenStage 40 SIP** have been certified with the German BLUE ANGEL label (valid from software version V2R2).

THE BLUE ANGEL is the first and oldest environment-related label for products and services.

The proprietor of this environmental label is the German Federal Ministry for the Environment, Nature Protection and Reactor Safety.

Siemens Enterprise Communications is the first company to fulfill the high standards of THE BLUE ANGEL in protecting the environment and the climate with its VoIP telephones. That is achieved by high energy efficiency, efficient use of materials as well as an environmentally friendly recycling and repair concept.

Further information can be found here:

<http://www.siemens-enterprise.com/de/about/green-enterprise.aspx>

http://www.blauer-engel.de/en/products_brands/search_products/produkttyp.php?id=559



OpenStage 15
ice blue



OpenStage 15
lava

OpenStage 20, 20 E

OpenStage 20 is a well equipped speaker-phone. With its intuitive and interactive user interface, it is a universal solution for efficient and professional telephony.

Display

- Tiltable graphical display, 2 lines monochrome

Keys

- Keypad
- 7 fixed function keys (partly equipped with red LEDs)
- Control keys +/-
- 3-way navigator

Acoustics

- Hands free talking (full duplex, OpenStage 20 only)
- Open listening (OpenStage 20, 20 E)

Wall-mountable

OpenStage 40

Customizable for various workplace environments, OpenStage 40 is recommended for use as an office phone, e.g. for desk sharing, people working in teams or call center staff.

Display

- Tiltable graphical display, 6 lines monochrome, backlit
- Optical call alert

Keys

- Keypad
- 8 fixed function keys (partly equipped with red LEDs)
- 6 freely programmable touch keys (illuminated) with red LEDs (function, speed dial or line keys)
- Control keys +/-
- 5-way navigator

Acoustics

- Hands free talking (full duplex)

Interfaces

- Headset jack

Wall-mountable

OpenStage 60 and 80

OpenStage 60

Offers top-notch functionality and innovations, combining a maximum of usability with a clear, intuitive and sleek design. An open application platform and personalization options make this phone the first choice for boss-secretary environments and people interacting with lots of other devices.

OpenStage 80

Premium features, materials and components turn this device into an extraordinary user experience. The best in class LCD display and an open platform for productivity enhancing applications unlock the full business potential of the phone. Open interfaces for easy synchronization with other devices, like PDA and mobile phone are specially designed with the needs of the top level manager and executive in mind.



OpenStage 20
ice blue



OpenStage 20
lava



OpenStage 20 E
ice blue



OpenStage 20 E
lava



OpenStage 40
ice blue



OpenStage 40
lava



OpenStage 60
ice blue



OpenStage 60
lava



OpenStage 80

Display

- OpenStage 60: Tilttable graphical color TFT display, 320 x 240 pixel (QVGA), backlit
- OpenStage 80: Tilttable graphical color TFT display, 640 x 480 pixel (VGA), backlit
- Optical call alert

Keys

- Keypad
- 6 fixed function keys (partly equipped with blue LEDs)
- 8 (OpenStage 60) and 9 (OpenStage 80) freely programmable touch keys (illuminated) with blue LEDs (function, speed dial or line keys)
- 6 mode keys (touch/sensor keys, illuminated) with blue or blue/white LEDs (e.g. to start applications)
- TouchSlider for volume adjustment with blue/white LEDs
- TouchGuide for navigation

Acoustics

- Hands free talking (full duplex)
- Polyphonic ring tones

Interfaces

- Headset jack
- Bluetooth
- USB Master

Accessories

For the respective OpenStage models a comprehensive range of accessories will be released separately. Here is a complete list of accessories:

OpenStage Key Module 15

- 18 additional freely programmable keys with LEDs; function, speed dial or line keys
- Paper labels
- In ice blue or lava
- For OpenStage 15/40 (up to 1 unit can be connected)



OpenStage Key Module 40, 60, 80

- 12 additional freely programmable keys with LEDs; function, speed dial or line keys (two-level)
- Large graphical display for key labeling
- In ice blue, lava or silver blue metallic
- For OpenStage 40, 60, 80 (up to 2 units can be connected)



OpenStage Busy Lamp Field 40

- 90 additional freely programmable keys with LEDs; function, speed dial or line keys
- Paper labels
- OpenStage 40 HFA only (not on HiPath 4000)
- In ice blue or lava
- For OpenStage 40 (only 1 unit can be connected)

Wall mount kit

- In ice blue or lava
- For OpenStage 20, 20 E, 40

OpenStage Manager

For administration of OpenStage 80 and 60, the OpenStage Manager offers the following functions:

- Administer OpenStage Phone Book
 - Synchronize contacts
 - Edit Phone Book
 - Add pictures
- Manage polyphonic ring tones
- Load screen saver pictures
- Configure OpenStage phone
- Backup/restore user data

OpenStage applications

OpenStage is an extremely powerful platform for efficient business applications.

The following applications are available with OpenStage 60, 80:

- Telephony
 - Context-sensitive menus
 - Simple use of complex phone features
- Personal phone book
 - Enter up to 1,000 personal contacts with different telephone numbers
 - Combine contacts into groups
 - Add a picture to favorite contacts
- Call log/history
 - See the list of missed, forwarded, dialed and received calls
 - Dial from the call log list
- Directory access (LDAP client)
 - Query corporate directories using LDAP
 - Quick search and advanced search with various search criteria
- Graphical voicemail control
 - Message waiting indication via LED and icon on idle screen
 - Intuitive user interface with tape recorder look & feel
 - Support with HiPath Xpressions V5.0, V6.0
- Bluetooth V2.0
 - Object Push profile: Send and receive business cards/vCards
 - Headset profile: Connect a Bluetooth headset
- Application platform for customer specific workflow integration
 - OpenStage 60/80 allows the customer to integrate own XML applications using the phone as an universal input/output device

HiPath Support

OpenStage SIP phones are supported by OpenScape Voice and Asterisk.

OpenStage CorNet-IP telephones can be operated on HiPath 3000/5000, HiPath 4000 and OpenScape Office LX/MX.

Access to the PSTN – Acoustic/Voice Quality

- FCC Part 68/CS-03 (Technical Requirements for Connection of Terminal Equipment to the Telephone Network)
- TIA/EIA-810A (Transmission Requirements for Narrowband VoIP and Voice over PCM Digital Wireline Telephones)
- TBR8 (Telephony 3.1 kHz teleservices – attachment requirements for handset terminals)
- Hearing aid capability (HAC) according TIA/EIA-504A (Electronic Industries Association recommended standard RS-504 magnetic field intensity criteria for telephone compatibility with hearing aids)

Technical Data

	OpenStage 15	OpenStage 20	OpenStage 40	OpenStage 60	OpenStage 80
Display					
Tiltable display (pixels, type)	2 lines, 205 x 41 pixels (not tiltable, fixed viewing angle of 30°)	2 lines, 205 x 41 pixels	6 lines, 240 x 128 pixels	320 x 240 pixels (QVGA) color TFT 5.7"	640 x 480 pixels (VGA) color TFT 6.4"
Backlit	–	–	Yes	Yes	Yes
Keys/LEDs					
Fixed function keys (pushbuttons, partly illuminated)	3 3 red LEDs	7 5 red LEDs	8 6 red LEDs	6 5 blue LEDs	6 5 blue LEDs
Freely programmable touch sensor keys (illuminated)	8 keys with red LEDs	–	6 keys with red LEDs	8 keys with blue LEDs	9 keys with blue LEDs
Mode keys (touch sensor keys, illuminated)	–	–	–	6 with blue or blue/white LEDs	6 with blue or blue/white LEDs
Optical call alert	–	–	red	blue	blue
Volume adjustment	+/- key	+/- key	+/- key	TouchSlider blue/white LEDs	TouchSlider blue/white LEDs
Navigation element	3 navigation keys	3-way navigator	5-way navigator	TouchGuide	TouchGuide
Interfaces					
Bluetooth V2.0 (vCard support and headset profile)	–	–	–	Yes	Yes
Headset jack for corded/cordless headsets	–	–	Yes	Yes	Yes
USB Master	–	–	–	Yes	Yes
OpenStage Key Module	Yes (max. 1)	–	Yes (max. 2)	Yes (max. 2)	Yes (max. 2)
OpenStage Busy Lamp Field (not for HiPath 4000, OpenStage 40 HFA only)	–	–	Yes (max. 1)	–	–
Integrated Ethernet switch	10/100 Base-T	10/100 Base-T or Gigabit Ethernet (optional variant) [not OpenStage 20 E]	10/100 Base-T or Gigabit Ethernet (optional variant)	10/100 Base-T or Gigabit Ethernet (optional variant)	10/100 Base-T or Gigabit Ethernet (optional variant)
Certifications					
	CE Mark, EMC EN55022 Class B, EN55024, EN61000-4-11, EN61000-3-2, Safety EN60950-1, North America EMC (FCC) Part 15 (CFR 47) Class B, Safety UL60950-1/CSA 22.2 No950				
Audio					
G.711 (64 kbit/s a/μ law)	Yes	Yes	Yes	Yes	Yes
G.722 (64 kbit/s)	Yes	Yes	Yes	Yes	Yes
G.729AB (8 kbit/s)	Yes	Yes	Yes	Yes	Yes
Open listening	Yes	Yes	Yes	Yes	Yes

	OpenStage 15	OpenStage 20	OpenStage 40	OpenStage 60	OpenStage 80
Full duplex hands-free	Yes	Yes (not OpenStage 20 E)	Yes	Yes	Yes
Echo canceling for local echo (AEC) full duplex	Yes	Yes (not OpenStage 20 E)	Yes	Yes	Yes
Applications					
See section "OpenStage applications"	–	–	–	Yes	Yes
Security features					
Layer 2 authentication (802.1x)	Yes	Yes	Yes	Yes	Yes
Network					
IEEE802.1Q	Yes	Yes	Yes	Yes	Yes
QoS (DIFFSERV and IEEE802.1p)	Yes	Yes	Yes	Yes	Yes
Power supply					
External power supply unit (EU, US or UK)	Yes	Yes	Yes	Yes	Yes
Power over LAN: IEEE 802.3af	Yes	Yes	Yes	Yes	Yes
PoL class	Class 1	Class 1	Class 2	Class 3	Class 3
Consumption data after annual load cycle according to RAL-UZ 150	22.8 kWh	21.7 kWh	25.3 kWh	35.6 kWh	30.7 kWh
Technical data					
Dimensions (height x width x depth [mm])	70 x 240 x 221	70 x 240 x 220	70 x 270 x 220	70 x 300 x 220	70 x 300 x 220
Weight (kg)	0.783	0.834	1.068	1.245	1.435
Colors	ice blue or lava	ice blue or lava	ice blue or lava	ice blue or lava	silver blue metallic
Storage conditions	-40 °C to +70 °C (-40 °F to 158 °F) [ETSI EN300 019-2-2]				
Operating conditions	+5 °C to +40 °C (41 °F to 104 °F)				

Your Siemens Partner:
MSGI Telecom Solutions
550 N. Reo St., Suite 300
Tampa, FL 33609
www.msgusa.com
ph 877-MSG USA1 - fx 877-MSG USA2

Copyright © Siemens Enterprise
Communications GmbH & Co. KG

**Siemens Enterprise
Communications GmbH & Co. KG
is a Trademark Licensee of Siemens AG**

Hofmannstr. 51, D-80200 München, 04/2011

Reference No.: A31002-S2000-D101-9-7629

The information provided in this document contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract. Subject to availability. Right of modification reserved.

The trademarks used are owned by Siemens Enterprise Communications GmbH & Co. KG or their respective owners.